

---

Subject: Re: SQLSRV Driver

Posted by [AJM](#) on Mon, 11 May 2015 08:21:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I can see two problems:

(1) You are not following the instructions at <http://www.tonymarston.net/php-mysql/infrastructure-faq.html#faq92> which clearly states that when you are using the multi-server option it is only the last entry which should have dbnames set to '\*' as this means "any database not identified in the previous entries". So the first entry should contain the following:

```
$servers[0]['dbnames'] = 'menu, audit, workflow, dict';
```

Each entry before the last one MUST identify the names of the databases which can be found on that server.

(2) You are not following the instructions at <http://www.tonymarston.net/php-mysql/sqlsrv.html#config.inc> which states that the server name should be set to "(local)" as in the following:

```
$servers[1]['dbengine']    = 'sqlsrv';  
$servers[1]['serverName']  = '(local)';  
$servers[1]['connectionInfo'] = array('CharacterSet' => 'UTF-8',  
                                       'ReturnDatesAsStrings' => true);  
$servers[1]['SQLSRV_schema'] = 'dbo';
```

Note: when you are using the \$servers array you do not need to use the \$GLOBALS array. Use one or the other, but not both.

---