

---

Subject: Re: xsl transformation slow

Posted by [braineyser](#) on Mon, 19 Mar 2007 15:18:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Just in case my ramblings have confused you a little, here is my final version of "display\_horizontal"

```
<!-- display details horizontally -->
<xsl:template name="display_horizontal">
<xsl:param name="zone"/>    <!-- could be 'main', 'inner', 'outer', etc -->
<xsl:param name="table_record" />
<xsl:param name="multiple"/> <!-- set this for more than one occurrence -->

<xsl:variable name="table" select="name()"/>      <!-- current table name -->
<xsl:variable name="position" select="position()"/> <!-- current row within table -->

<tr>
  <!-- set the row class to 'odd' or 'even' to determine the colour -->
  <xsl:attribute name="class">
    <xsl:choose>
      <xsl:when test="position()mod 2">odd</xsl:when>
      <xsl:otherwise>even</xsl:otherwise>
    </xsl:choose>
  </xsl:attribute>

<!-- step through the fields defined in the STRUCTURE element -->
<xsl:for-each select="/root/structure/*[name()=$zone]/row/cell[@field]">

  <!-- get fieldname from the FIELD attribute -->
  <xsl:variable name="fieldname" select="@field" />

  <!-- select the field (identified in STRUCTURE) from the current row of the specified table -->
  <xsl:variable name="field" select="$table_record/*[name()=$fieldname]" />

  <td>
    <!-- process the named field from the current row -->
    <xsl:call-template name="datafield">
      <xsl:with-param name="item" select="$field"/>
      <xsl:with-param name="itemname" select="$fieldname"/>
      <xsl:with-param name="path" select="$table"/>
      <xsl:with-param name="multiple" select="$multiple"/>
      <xsl:with-param name="position" select="$position"/>
    </xsl:call-template>
  </td>

</xsl:for-each>
</tr>
```

```
</xsl:template> <!-- display_horizontal -->
```

and this is the change needed in the calling scripts to make it work...

std.link1.xsl

```
<!-- process each non-empty row in the MAIN table of the XML file -->
<xsl:for-each select="/*[name()=$main][count(*)>0]">

    <!-- display all the fields in the current row -->
    <xsl:call-template name="display_horizontal">
        <xsl:with-param name="zone" select="main"/>
    <xsl:with-param name="table_record" select=". " /> <!-- ADD THIS LINE TO ALL CALLING
SCRIPTS -->
    </xsl:call-template>
</xsl:for_each>
```

similar change in std.link1.xsl

```
<!-- process each non-empty row in the INNER/CHILD table of the XML file -->
<xsl:for-each select="/*[name()=$link][count(*)>0]">

    <!-- display all the fields in the current row -->
    <xsl:call-template name="display_horizontal">
        <xsl:with-param name="zone" select="link"/>
    <xsl:with-param name="table_record" select=". " />
        <xsl:with-param name="multiple" select="y"/>
    </xsl:call-template>

</xsl:for_each>
```

etc etc...

Seems to work correctly. And it's lightning fast. Give it a whirl, what's the worst that could happen?