
Subject: ERROR CREATING WHERE CLAUSE WHEN USING SEARCH

Posted by [edortizq](#) on Tue, 16 Oct 2018 06:30:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have the tables in the attached file tables.sql

And this code in detaileventa.class.inc:

```
function _cm_changeConfig ($where, $fieldarray) {
    // $this->fieldspec['idtarifa']['noedit']='y';
    $this->fieldspec['valortickets']['noedit']='y';
    if ($GLOBALS['mode'] == 'search') {
        unset($this->fieldspec['fechaventa']);
        unset($this->fieldspec['nombrerazonsocial']['noedit']);
        unset($this->fieldspec['idtarifa']['noedit']);
        unset($this->fieldspec['usuarioturnocaja']['noedit']);
        unset($this->fieldspec['cantidadtickets']['noedit']);

        $this->fieldspec['date_from'] = array('type' => 'date',
                                              'size' => 12);
        $this->fieldspec['date_to'] = array('type' => 'date',
                                            'size' => 12);
    }

    if ($GLOBALS['mode'] == 'list' || $GLOBALS['mode'] == 'read') {
        $this->fieldspec['numfactura'] = array ('type'=> 'string',
                                                'size'=> 18,
                                                'nondb'=>'y');
    }

    if ($GLOBALS['mode'] == 'list' || $GLOBALS['mode'] == 'read' || $GLOBALS['mode'] ==
'search' ) {
        $this->fieldspec['venta.idturnocaja'] = array('type' => 'integer',
                                                       'size' => 11);
        $this->fieldspec['usuarioturnocaja'] = array('type' => 'string',
                                                       'size' => 16);
        $this->fieldspec['nombrerazonsocial'] = array('type' => 'string',
                                                       'size' => 64);
    }

    if ($GLOBALS['task_id'] == 'buzz_detaileventa(add5)'){
        // insert some javascript to submit form when a different value is selected in this dropdown
        list
            $this->fieldspec['idtarifa']['javascript'] = array('onchange' => 'this.form.submit();');
            $this->fieldspec['cantidadtickets']['javascript'] = array('onchange' => 'this.form.submit();');
            // $GLOBALS['act_buttons']['submitBtn'] = "GRABAR";
            unset ($GLOBALS['act_buttons']['submitBtn']);
    }
}
```

```

unset ($GLOBALS['act_buttons']['submitstay']);
$GLOBALS['act_buttons']['submitnext'] = "GRABAR-IMPRIMIR";

} // if

return $fieldarray;
}

function _cm_pre_getData ($where, $where_array, $parent_data=null) {

$previous_tast = getPreviousTask();
if ($GLOBALS['task_id'] == 'buzz_detallevanta(output4)' && $previous_tast ==
'buzz_venta(list2)caja'){
    $where = $_SESSION['whereCSV'];
}

$newWhere = NULL;

if (!empty($this->sql_search)) {
    // convert from string to an associative array
    $fieldarray = where2array($this->sql_search, false, false);
    // deal with values which have ranges
    if (!empty($fieldarray['date_from']) OR !empty($fieldarray['date_to'])) {
        $fieldarray['fechaventa'] = rangeFromTo($fieldarray['date_from'], $fieldarray['date_to'],
true);
        unset($fieldarray['date_from']);
        unset($fieldarray['date_to']);
    } // if
    $newWhere = array2where($fieldarray);
} // if

if ($GLOBALS['task_id'] == 'buzz_detallevanta(list1')){
// insert some javascript to submit form when a different value is selected in this dropdown
list
    $this->sql_orderby = "fechaventa";
    $this->sql_orderby_seq = "desc";
} // if
if ($GLOBALS['mode'] == 'list' || $GLOBALS['mode'] == 'read' || $GLOBALS['mode'] ==
'search' || $GLOBALS['mode'] == 'csv') {
    $this->sql_select = " iddetalleventa,venta.fechaventa,cliente.nombrerazonsocial,if
(venta.tipocomprobante=1,'FACTURA','PASE A BORDO') as tipo,";
    $this->sql_select .= ' formapago.descripcionformapago,venta.establecimiento,venta.
puntoemision,venta.secuenciasri,';
    $this->sql_select .= ' idtarifa,cantidadtickets,valortickets,venta.idturnocaja,tur
nocaja.usuarioturnocaja';
    $this->sql_from = 'detalleventa LEFT JOIN venta ON (detalleventa.idventa =
venta.idventa)';
    $this->sql_from .= ' LEFT JOIN cliente ON (venta.idcliente = cliente.idcliente)';
}

```

```

$this->sql_from .= ' LEFT JOIN formapago ON (venta.idformapago =
formapago.idformapago)';
$this->sql_from .= ' LEFT JOIN turnocaja ON (venta.idturnocaja = turnocaja.idturnocaja)';
if (isset ($newWhere)) {
    $this->sql_where = $newWhere;
    $where = $newWhere;
}
return $where;
}

```

When I try a search over usuarioturnocaja field the framework creates the following mistaken sql statement:

```

SELECT SQL_CALC_FOUND_ROWS iddetalleventa, venta.fechaventa,
cliente.nombrerazonsocial,
if(venta.tipocomprobante=1,'FACTURA','PASE A BORDO') AS tipo,
formapago.descripcionformapago,
venta.establecimiento, venta.puntoemision, venta.secuenciasri, idtarifa, cantidadtickets,
valortickets,
venta.idturnocaja, turnocaja.usuarioturnocaja
FROM detalleventa
LEFT JOIN venta ON (detalleventa.idventa = venta.idventa)
LEFT JOIN cliente ON (venta.idcliente = cliente.idcliente)
LEFT JOIN formapago ON (venta.idformapago = formapago.idformapago)
LEFT JOIN turnocaja ON (venta.idturnocaja = turnocaja.idturnocaja)
WHERE detalleventa.idtarifa= 2 AND detalleventa.usuarioturnocaja LIKE 'CAJA01%'
ORDER BY venta.fechaventa desc
LIMIT 10 OFFSET 0

```

Note that in the where clause the field usuarioturnocaja is qualified with the detalleventa table when it should be qualified with turnocaja table.

File Attachments

-
- 1) [tables.sql](#), downloaded 622 times
-