Subject: Re: PopUp and add1 - key fields
Posted by htManager on Fri, 18 Dec 2015 16:08:04 GMT
View Forum Message <> Reply to Message

I do know and understand what you mean but I can't get the code right. I worked through two more php tutorials but I don't succeed. Here is my code, can you take a look at it?

Why can't I change the status of $popupaufruf_status? Is it because of the visibility of the variable? Thank you very much in advance.

```
<?php
require_once 'std.table.class.inc';
class orga_kontakte_adresse extends Default_Table
{
    public $popupaufruf_status = False;

    //  ********************************************************** ****************
    function orga_kontakte_adresse ()
    {
        // save directory name of current script
        $this->dirname   = dirname(__file__);

        $this->dbms_engine = '';            // to be supplied by getFieldSpec_original()
        $this->dbprefix    = '';           // to be supplied by getFieldSpec_original()
        $this->dbname      = 'htm';
        $this->tablename   = 'orga_kontakte_adresse';

        // call this method to get original field specifications
        // (note that they may be modified at runtime)
        $this->fieldspec = $this->getFieldSpec_original();

    } // kontakte

    function _cm_getInitialData ($fieldarray)
    // Perform custom processing for the getInitialData method.
    // $fieldarray contains data from the initial $where clause.
    {
     {
      if ($popupaufruf_status == True) {
       echo 'Wahre Welt';
      }
      elseif ($popupaufruf_status == False) {
       echo 'Falsche Welt';

       // get next available number for user_seq_no
       $where = "user_id='{$_SESSION['logon_user_id']}'";
       $query = "SELECT max(user_seq_no) FROM $this->tablename WHERE $where";
       $count = $this->getCount($query);
```

```
   $fieldarray['user_id'] = $_SESSION['logon_user_id'];
   $fieldarray['user_seq_no']  = $count + 1;
  }
 }

    // set these fields to 'noedit' (read only)
    $this->fieldspec['user_id']['noedit']  = 'y';
    $this->fieldspec['user_seq_no']['noedit'] = 'y';

    return $fieldarray;

} // _cm_getInitialData

function _cm_popupCall ($popupname, $where, $fieldarray, &$settings)
// if a popup button has been pressed the contents of $where may need to
// be altered before the popup screen is called.
// NOTE: $settings is passed BY REFERENCE as it may be altered.
{
 // allow only one entry to be selected (the default)
 $settings['select_one'] = FALSE;

 return $where;

} // _cm_popupCall

//  ********************************************************** ****************
function _cm_popupReturn ($fieldarray, $return_from, &$select_array, $return_files)
// process a selection returned from a popup screen.
// $fieldarray contains the record data when the popup button was pressed.
// $return_from identifies which popup screen was called.
// $select_array contains an array of item(s) selected in that popup screen.
// $return_files contains a list of all files loaded via a fileupload task.
// NOTE: $select_array is passed BY REFERENCE so that it can be modified.
{
 //if ($return_from == '???(popup)') {
 //    // change field name from 'foo_id' to 'bar_id'
 //    $select_array['bar_id'] = $select_array['foo_id'];
 //    unset($select_array['foo_id']);
 //} // if

 // Variable fÃ¼r _cm_GetInitialData, dass Daten aus Kontakt-Pool Ã¼bernommen werden
 $this->popupaufruf_status(True);

 return $fieldarray;

} // _cm_popupReturn
```

```
    //  ************************************************************ ****************
    function _cm_post_popupReturn ($fieldarray, $return_from, $select_array)
    {

     // liest Daten in AbhÃ¤ngigkeit des aufrufenden Formulars ein
     if ($return_from == 'htm_orga_kontakte(popup1)'){

      // get contents of foreign table KONTAKTE
      $dbobject =& RDCsingleton::getInstance('orga_kontakte'); // Instanz fÃ¼r Lookup-Tabelle
      $where = "user_id='{$select_array['user_id']}'
         AND user_seq_no='{$select_array['user_seq_no']}'
         AND rdcaccount_id='{$select_array['rdcaccount_id']}'";
      $data = $dbobject->getData ($where);

      if (!empty($data)){
       $data = $data[0];
        $fieldarray['user_id'] = $data['user_id'];
     $fieldarray['user_seq_no'] = $data['user_seq_no'];
        $fieldarray['rdcaccount_id'] = $_SESSION['rdcaccount_id'];
     $fieldarray['kontakt_name'] = $data['kontakt_name'];
        $fieldarray['kontakt_vorname'] = $data['kontakt_vorname'];
        $fieldarray['kontakt_middlename'] = $data['kontakt_middlename'];
           $fieldarray['kontakt_geburtstag'] = $data['kontakt_geburtstag'];
       } // if
      }

      return $fieldarray;

    }

    //  ************************************************************ ****************
    function popupaufruf_status($neuer_status) {
     // Ã¤ndert die Eigenschaft von $popupaufruf
     $this->popupaufruf_status = $neuer_status;
    }

//    function __construct($neuer_status){
//     $this->popupaufruf_status = $neuer_status;
//    }

//  ************************************************************ ****************
} // end class
//  ************************************************************ ****************

// Variable fÃ¼r _cm_GetInitialData, dass Daten aus Kontakt-Pool Ã¼bernommen werden
$popupobject = new orga_kontakte_adresse();

?>
```