Subject: Re: Check for empty $schema in dml.psql.class.inc
Posted by pdv on Sun, 10 Feb 2019 16:16:34 GMT
View Forum Message <> Reply to Message

Unfortunately I cannot reproduce the problem without first removing my test-database (bxtests): I have reactivated the check for !empty($schema) and there is no more problem. But I notice that &_getDBMSengineByHost() is not called anymore, just &_getDBMSengine() and that might explain the difference.

The problem occurred when I tried to import my bxtests database for the very first time, using the 2-server configuration I've send previously.

Luckily I kept the relevant error-message which shows that __construct is called with an empty $dbname. And indeed I don't see right away where in &_getDBMSengineByHost(), $args['dbname'] has been set before calling the constructor.

2019-01-26 21:59:33
Fatal Error: No value supplied for PGSQL_dbname (# 256)
Error in line 93 of file '/Library/WebServer/Documents/radicore/includes/dml.pgsql.cl ass.inc'.
PHP_SELF: /radicore/dict/database(add1)import.php
CURRENT DIRECTORY: /Library/WebServer/Documents/radicore/dict
SERVER_ADDR: ::1
SERVER_NAME: localhost
HTTP_HOST: localhost
User Id: MGR
Role Id: GLOBAL
REMOTE_ADDR: ::1
REQUEST_URI: /radicore/dict/database(add1)import.php?csrf_id=5c4cd84538cc89.99819281&session_name=menu1

Page Stack:

[0] main_menu
[1] dictionary
[2] dict_database(list1)
[3] dict_database(add1)import

Backtrace:
0: array =
function: string = errorHandler
args: array =
0: integer = 256
1: string = No value supplied for PGSQL_dbname
2: string = /Library/WebServer/Documents/radicore/includes/dml.pgsql.cla ss.inc
3: integer = 93
4: array =
args: array =

```
        dbhost: string = localhost
        dbusername: string = theusername1
        dbuserpass: string = thepassword1
        dbprefix: string =
        PGSQL_dbname: string = bxtests
        dbname: string = null
        dbport: string = null
        dbsocket: string = null
      schema: string = null
1: array =
 file: string =  /Library/WebServer/Documents/radicore/includes/dml.pgsql.cla ss.inc
 line: integer = 93
 function: string = trigger_error
 args: array =
   0: string = No value supplied for PGSQL_dbname
   1: integer = 256
2: array =
 file: string =  /Library/WebServer/Documents/radicore/includes/std.singleton .php5.inc
 line: integer = 131
 function: string = __construct
 class: string = pgsql
 type: string = ->
 args: array =
   0: array =
     dbhost: string = localhost
     dbusername: string = theusername1
     dbuserpass: string = thepassword1
     dbprefix: string =
     PGSQL_dbname: string = bxtests
     dbname: string = null
     dbport: string = null
     dbsocket: string = null
3: array =
 file: string =  /Library/WebServer/Documents/radicore/dict/classes/dict_data base_s01.class.inc
 line: integer = 336
 function: string = getInstance
 class: string = RDCsingleton
 type: string = ::
 args: array =
   0: string = pgsql
   1: array =
     dbhost: string = localhost
     dbusername: string = theusername1
     dbuserpass: string = thepassword1
     dbprefix: string =
     PGSQL_dbname: string = bxtests
   2: boolean = 1
4: array =
```

file: string = /Library/WebServer/Documents/radicore/dict/classes/dict_data base_s01.class.inc
line: integer = 166
function: string = _getDBMSengineByHost
class: string = dict_dataBase_s01
type: string = ->
args: array =
0: string = localhost
5: array =
file: string = /Library/WebServer/Documents/radicore/dict/classes/dict_data base_s01.class.inc
line: integer = 90
function: string = _loadDatabases
class: string = dict_dataBase_s01
type: string = ->
args: array =
0: string = localhost
1: array =
2: string =
3: array =
4: array =
public: string = bxtests
6: array =
file: string = /Library/WebServer/Documents/radicore/includes/std.table.cla ss.inc
line: integer = 3276
function: string = _cm_getInitialData
class: string = dict_dataBase_s01
type: string = ->
args: array =
0: array =
7: array =
file: string = /Library/WebServer/Documents/radicore/includes/std.add1.inc
line: integer = 60
function: string = getInitialData
class: string = Default_Table
type: string = ->
args: array =
0: string =
8: array =
file: string = /Library/WebServer/Documents/radicore/dict/database(add1)imp ort.php
line: integer = 9
args: array =
0: string = /Library/WebServer/Documents/radicore/includes/std.add1.inc
function: string = require_once