Subject: Re: Fatal Error: %1$s (# %2$s).
Posted by danpoleary on Wed, 16 May 2007 17:42:14 GMT
View Forum Message <> Reply to Message

Thanks Tony,

I uncommented the line indicated, and here is what is logged:

<h2>2007-05-16 13:38:46</h2> Fatal Error: %1$s (# %2$s). Error in line 278 of file '/data/www/html/search/includes/dml.mysqli.class.inc'. Script: /search/search/configuration(add1).php User Id: MGR Remote Address: 142.101.244.26 Request URI: /search/search/configuration(add1).php
Page Stack:
<pre>
[0] main_menu
[1] sanitize
[2] san_configuration(list1)
[3] san_configuration(add1)

</pre>
<pre>
0: array =
function: string = errorHandler
args: array =
0: integer = 256
1: string = SQL
2: string = /data/www/html/search/includes/dml.mysqli.class.inc
3: integer = 278
4: array =
dbname: string = sanitizer
tablename: string = configuration
where: string = SELECT count(*) FROM configuration WHERE *NO PRIMARY KEY HAS BEEN DEFINED*
result: boolean =
1: array =
file: string = /data/www/html/search/includes/dml.mysqli.class.inc
line: integer = 278
function: string = trigger_error
args: array =
0: string = SQL
1: integer = 256
2: array =
file: string = /data/www/html/search/includes/dml.mysqli.class.inc
line: integer = 691
function: string = getCount
class: string = mysql
object: object = Object id #2
type: string = ->

```
  args: array =
    0: string = sanitizer
    1: string = configuration
    2: string = SELECT count(*) FROM configuration WHERE *NO PRIMARY KEY HAS BEEN
DEFINED*
3: array =
  file: string = /data/www/html/search/includes/std.table.class.inc
  line: integer = 4127
  function: string = insertRecord
  class: string = mysql
  object: object = Object id #2
  type: string = ->
  args: array =
    0: string = sanitizer
    1: string = configuration
    2: array =
      parameter: string = testit
      value: string = /testit
4: array =
  file: string = /data/www/html/search/includes/std.table.class.inc
  line: integer = 2058
  function: string = _dml_insertRecord
  class: string = Default_Table
  object: object = Object id #6
  type: string = ->
  args: array =
    0: array =
      parameter: string = testit
      value: string = /testit
5: array =
  file: string = /data/www/html/search/includes/std.add1.inc
  line: integer = 90
  function: string = insertRecord
  class: string = Default_Table
  object: object = Object id #6
  type: string = ->
  args: array =
    0: array =
      parameter: string = testit
      value: string = /testit
6: array =
  file: string = /data/www/html/search/search/configuration(add1).php
  line: integer = 9
  args: array =
    0: string = /data/www/html/search/includes/std.add1.inc
  function: string = require

</pre>
```

Let me know if you need anything else

Dan