Subject: Re: Update 4
Posted by danpoleary on Mon, 09 Jul 2007 19:16:14 GMT
View Forum Message <> Reply to Message

Hi Tony,

Sorry, I based that call on something on say in the existing code.

I now have the following in the inner entity (filelist_auto.class.inc file) which extends the filelist.class.inc. This extended class is used in both the multi4, and in the update4.

Quote:
```
    function _cm_pre_updateRecord($rowdata)
   {
          $rowdata['autopublish'] = TRUE;

          // what was select in the popup during _cm_initialize
          $rowdata['publish_key'] = $rowdata['sel_publish_key'];
          return $rowdata;
   }

  function _cm_changeConfig ($where, $fieldarray)
   {
    $fieldarray['sel_publish_key'] = '';
    $this->fieldspec['sel_publish_key'] = array('type' => 'string',
                                          'size' => 32);
     return $fieldarray;

   }

    function _cm_getInitialData ($fieldarray)
    // Perform custom processing for the getInitialData method.
    // $fieldarray contains data from the initial $where clause.
    {
       $fieldarray['sel_publish_key'] = $_POST['sel_publish_key'];

       return $fieldarray;

    } // _cm_getInitialData

    function _cm_getPkeyNames ($pkey, $task_id, $pattern_id)
    {
       $pkey_array[] = 'sel_publish_key';
       return $pkey_array;
    }
```

Where else could I try? I can see the post of the sel_publish_key, but I am not sure in which function to set it!

I have looked for many examples, but have yet to find one that works in this multi4, update4 fashion.

Thanks,

dan
