Subject: Incorrect CSS settings
Posted by ljkbrost on Fri, 14 Apr 2006 06:08:03 GMT
View Forum Message <> Reply to Message

I run my apache server on http://localhost:8080 and I found a problem with the XML that gets sent to the client. It looks like the system is not sending the port for the machine.

<cssfiles> <filename>HTTP://localhost/radicore/style_default.css</filename>
<filename>HTTP://localhost/radicore/menu/style_custom.css</filename>
</cssfiles>

I have traced the problem to include.xml.php?.inc inside of the setCSSfiles(...) function. When building the filename values the string building function uses $_SERVER['SERVER_NAME'] when it should use $_SERVER['HTTP_HOST'].

Altering the code to the following resolved my problems:

```
    // if no custom stylesheet is specified use 'style_custom.css' in local directory
    if (empty($css_files)) {
        $css_files[] = 'HTTP://' .$_SERVER['HTTP_HOST'] .dirname($_SERVER['PHP_SELF'])
.'/style_custom.css';
    } // if

    // prepend the default stylesheet name from base directory
    $dir = getParentDIR();
    if (!empty($_SERVER['HTTPS'])) {
        $default_css = 'HTTP://' .$GLOBALS['https_server'] .$GLOBALS['https_server_suffix'] .$dir
.'/style_default.css';
    } else {
        $default_css = 'HTTP://' .$_SERVER['HTTP_HOST'] .$dir .'/style_default.css';
    } // if
```

Cheers,

Kyle Brost

Subject: Re: Incorrect CSS settings
Posted by AJM on Fri, 14 Apr 2006 10:05:42 GMT
View Forum Message <> Reply to Message

Thanks for spotting that. It's always confusing when to use $_SERVER['HTTP_HOST'] and $_SERVER['SERVER_NAME'] as they supposedly give the same results except under circumstanes which are not documented.

I shall change my code for the next release.